



ALL MEASUREMENTS ARE CENTER TO CENTER

## **HIGH-N-DRY 15,000 LB. GENERAL SPECS**

|                                   |   |
|-----------------------------------|---|
| <b>Piling size</b>                | <b>4ea. 8" or larger dia</b>  |
| <b>Piling Height Requirements</b> | <b>24" above the deck, minimum</b>  |
| <b>Power Requirements</b>         | <b>110volt 30amp minimum / 220 volts, 15 amps</b>   |
| <b>Motor Specs</b>                | <b>2 - 3/4 HP 1750 RPM</b>  |
| <b>Switching Gear</b>             | <b>2 Independent Manual Bremas Switches<br/>OPTIONAL: Wireless Remote Control with or without Auto Shut-Off</b> |
| <b>Cable Size</b>                 | <b>7x19 Stainless Steel , 5/16 diameter 9' travel standard,<br/>Longer Cable available on request</b>           |
| <b>Cradle Beams</b>               | <b>2ea. W8" x 4" x 15 lb. per foot Galvanized Steel I Beam, class 50</b>  |
| <b>Bunks</b>                      | <b>HD : 2 ea. Galvanized Steel I Beam Reinforced 4x6x16' Timbers</b>  |
| <b>Drive Units</b>                | <b>2 ea. AMS 3000 Worm Gear Drives with Galvanized Backing Plates<br/>OPTIONAL: E-Gear Drives</b>               |
| <b>Boat Positioning</b>           | <b>4 ea. 8' PVC Guide Stantions with Caps<br/>HD : Elevated Outboard Walkway</b>                                |